




## ZA TYPE (OXYGEN & ACETYLENE QUICK COUPLING) FOR CUTTER USE



Major Applicable Fluid~ Brass=Iron: Oxygen / Acetylene / Air

blocked

Computer No	Product Sign	Dimension (mm)						Weight (g)	Quantity per Carton
		Lp	C	Zp	A	T	Bp		
AOOZJAZO	P-2	44.6	20.8	Ø21.8*6HEX*19D	10.6	M16*1.5PL	4.6	39	50-A

unblocked

Computer No	Product Sign	Dimension (mm)						Weight (g)	Quantity per Carton
		Lp	C	Zp	A	T	Bp		
AOOZJAZO	P-B	44.6	20.8	Ø21.8*6HEX*19D	10.6	M16*1.5PL	4.6	37	50-A

Computer No	Product Sign	Dimension (mm)						Weight (g)	Quantity per Carton
		Ls	D	Hs	A	T	Bs		
AOOZJAAS	20T	48	22	Ø19.5*6HEX*17D	10	M16*1.5PL	6	66	50-A

Computer No	Product Sign	Dimension (mm)						Weight (g)	Quantity per Carton
		Ls	D	A	T	Hs	Bs		
AOOZJAAS	206	67.6	22	24	6.5	13	3	61	50-A
AOOZJAAS	208	69.6	22	26	9	13	5	63	50-A

blocked

Computer No	Product Sign	Dimension (mm)						Weight (g)	Quantity per Carton
		Lp	C	Zp	A	T	Bp		
AOOZJAZO	P-1	44.6	20.4	Ø21.8*6HEX*19D	10.6	M16*1.5P	3.6	39	50-A

unblocked

Computer No	Product Sign	Dimension (mm)						Weight (g)	Quantity per Carton
		Lp	C	Zp	A	T	Bp		
AOOZJAZO	P-A	44.6	20.4	Ø21.8*6HEX*19D	10.6	M16*1.5P	3.6	37	50-A

Computer No	Product Sign	Dimension (mm)						Weight (g)	Quantity per Carton
		Ls	D	Hs	A	T	Bs		
AOOZJAAS	10T	46	20	Ø19.5*6HEX*17D	10	M16*1.5P	6	62	50-A

Computer No	Product Sign	Dimension (mm)						Weight (g)	Quantity per Carton
		Ls	D	A	T	Hs	Bs		
AOOZJAAS	106	65.6	20	24	6.5	11	3	52	50-A
AOOZJAAS	108	67.6	20	26	9	11	5	54	50-A

Max. pressure: 10Kg/cm<sup>2</sup>

Special seal(Packing) temperature range: -50°C ~ +300°C

Uses: Active / Inertia / Chemical Gas · Vehicle · Mark For Piping Operating temp. range: -20°C ~ +80°C